

45D ORANGE

ADVANCED CONVEYOR BELT SPLICING TECHNOLOGY



45D Orange is produced using a 45 durometer natural rubber blend. This will result in less belt wear and longer belt life.



It is orange in color and easily conforms to most all trough belt configurations.

45D Orange	1/2" x 4" x 50'
45D Orange	1/2" x 6" x 50'
45D Orange	1/2" x 8" x 50'
45D Orange	3/8" x 4" x 50'
45D Orange	3/8" x 6" x 50'
45D Orange	3/8" x 8" x 50'

RUBBER COMPOUND WITH THEIR PHYSICAL PROPERTIES 45D Orange

S. No	Rubber Characteristic	Units	Test Norm	Specified Value 45D Orange
1.	Tensile Strength	MPa	ISO 37	20.00 Min.
2.	Elong. at Break	%	ISO 37	600 Mi
3.	Shore Hardness	°A	ISO 48-4	45 + 5
4.	Density	g/cm ³	ISO 2781	1.08 + 0.03
5.	Abrasion Loss at 5 N	mm ³	ISO 4649	80 Max.
6.	Tear Strength	N/mm	ISO 34-1	60 Min.

PLANT 1: 21611 W SR 51 Genoa, OH 43430
 PLANT 2: 504 E. Front St. Pemberville, OH 43450
 SALES & SUPPORT: (419) 287-7092
 FAX: (419) 691-7688
 SALES & SUPPORT EMAIL: info@nbeltingss.com

N **NATIONWIDE
 BELTING SALES
 AND SERVICES**