

# 2 PLY 100# WHITE ESF URETHANE BARE x BARE NON FRAY

CODE NUMBER: 9910



## TECHNICAL DATA

Color	White
Compound	Spun Polyester Fabric
Plies	2
Fabric/Carcass	Spun Polyester Fabric
Cover Surface	Impregnated Fabric
Bottom Surface	Impregnated Fabric
Working Strength	100#
Overall Gauge	.051"
Weight PIW	.025 lbs/ft <sup>2</sup>
Minimum Pulley	.394"
Temp Range ° F	-22° - 176° F
FDA/USDA	Yes/No
Anti-Static	No
Recommended Splice	Endless, Clipper®, Staple
Maximum Width	124.75"

### Feature/Benefits:

This belt is used in a wide variety of food processing applications. The belt surface makes it a popular choice for rolling and forming, as well as cutting and packing applications. Excellent flexibility, splicing strength and appearance.

PLANT 1: 21611 W SR 51 Genoa, OH 43430  
PLANT 2: 504 E. Front St. Pemberville, OH 43450  
SALES & SUPPORT: (419) 287-7092  
FAX: (419) 691-7688  
SALES & SUPPORT EMAIL: [info@nbeltingss.com](mailto:info@nbeltingss.com)

**N**ATIONWIDE  
BELTING SALES  
AND SERVICES