

# 1 PLY 120# POLYESTER BLACK NEEDLED NITRILE FRICTION x FRICTION .140 THICK

CODE NUMBER: 8450



TECHNICAL DATA	
Color	Black
Compound	Polyester
Plies	1
Fabric/Carcass	Polyester
Cover Surface	Impregnated Polyester
Bottom Surface	Impregnated Polyester
Working Strength	100#
Overall Gauge	.1"
Weight PIW	.0237
Minimum Pulley	1"
Temp Range ° F	-4° - 248° F
FDA/USDA	No
Anti-Static	No
Recommended Splice	Finger
Maximum Width	78"

#### Feature/Benefits:

Wear and cut resistant, soft impact surface, high temperature resistant, quiet running, high conductive on upper/lower side and through. Abrasion resistant, accumulation, airports, distribution centers, general conveying, horticultural, industrial, material handling, metal parts, mineral oil, nuts and seeds, recycling, troughed applications, turn applications.

PLANT 1: 21611 W SR 51 Genoa, OH 43430  
PLANT 2: 504 E. Front St. Pemberville, OH 43450  
SALES & SUPPORT: (419) 287-7092  
FAX: (419) 691-7688  
SALES & SUPPORT EMAIL: [info@nbeltingss.com](mailto:info@nbeltingss.com)

**N**ATIONWIDE  
BELTING SALES  
AND SERVICES